

Laser-Based Diagnostic Measurements of Low Emissions Combustor Concepts

This presentation provides a summary of primarily laser-based measurement techniques we use at NASA Glenn Research Center to characterize fuel injection, fuel/air mixing, and combustion. The report highlights using Planar Laser-Induced Fluorescence, Particle Image Velocimetry, and Phase Doppler Interferometry to obtain fuel injector patternation, fuel and air velocities, and fuel drop sizes and turbulence intensities during combustion. We also present a brief comparison between combustors burning standard JP-8 Jet fuel and an alternative fuels. For this comparison, we used flame chemiluminescence and high speed imaging.




Laser-Based Diagnostic Measurements of Low Emissions Combustor Concepts

Dr. Yolanda R. Hicks


**Research Engineer
NASA Glenn Research Center**

*Dr. Randy J. Locke
Robert C. Anderson
Christopher M. Heath*



2011 Technical Conference
NASA Fundamental Aeronautics Program
Subsonic Fixed Wing Project
Cleveland, OH, March 15 - 17, 2011




Diagnostics Objectives: Support efforts to produce next generation low emission combustor technology







Use and develop tools to facilitate understanding of the fuel vaporization, turbulent mixing and combustion processes within aircraft combustors

Describe overall performance:

- Characterize fuel injection-fuel/air mixing
- Characterize combustion
- Provide data to validate models





COMBUSTOR FLOW PHENOMENA



Example systems



- Complex Swirl Mixers
- NASA Lean Direct Injector (LDI)
low emissions technology research injector



CE-5 Combustor Subcomponent Test Facility



- Two Separate Test Legs
- Dual Fuel Capability w/On-Line Blending
 - Gaseous and Particulate Emissions
- Windowed Test Sections
 - Laser Diagnostics
 - High Speed Imaging




NASA multipoint LDI injector

Pressures: up to 275 psia (windows) or 450 psia
Inlet Temperature: 505 K (450 ° F) – 827 K (1030 ° F)

W_{air} : up to 10 pps



A complex swirl-cup injector




Optical Diagnostics Measurement Suite




Species, temp via PLIF, elastic scatter, Raman scatter

- *2D, 3D mapping of: OH, NO, fuel liquid and vapor
CH, profile and pattern factor*
- *1D mapping of major combustion species:
CO₂, O₂, N₂, hydrocarbons, H₂O*




Global Chemiluminescence Imaging of C₂, CH, OH, NO



Velocity

- *2 component mapping via images—PIV*
- *3 component pointwise—LDV/PDI*




Drop Sizing



- *3 component pointwise—PDI*
- *shadowgraph-based, long range microscope*

Flow/flame visualizations

movies: video, high speed photography, schlieren








Typical Imaging Setup



3D Phase Doppler Interferometry



- 3-color, 6 beams in a 5 beam layout
Center has one blue and one green collinear




Examples



- Fuel Mass/Pattern Comparison CFD, Fuel PLIF
- Particle Image Velocimetry, Air and Fuel drop velocities
- Phase Doppler Interferometry—Drop sizes, velocities, Turb Int.
- Alternative Fuel Comparison using high speed flame imaging, chemiluminescence


Coordinate & Setup Definitions



+ X (Out of Page)
"End View"

Test Space Coordinate Definition


$X \rightarrow$ Axial Flow Direction (U-Velocity)
 $Y \rightarrow$ Lateral Flow Direction (V-Velocity)
 $Z \rightarrow$ Vertical flow Direction (W-Velocity)



Fuel Pattern/Fuel Mass Comparison NASA Data: Fuel PLIF



*Comparing primarily flow in the main injector region,
which has several discrete injection points*



Velocity, drop size measurements, LDI injector

Air only, 2-D velocity measurements, PIV


- “instantaneous” (5- μ sec Δt) vector fields
- Average results


Fueled, combusting results, PDI and PIV

Ten Consecutive Instantaneous PIV Axial-Vertical Velocity Fields



Air only. $T_3 = 1030^\circ \text{ F}$, $P_3 = 150 \text{ psia}$







2D velocity

RMS velocity




vertical distance from centerline, mm



- Recirc zones directly downstream of injectors
- Black bands—location of zero velocity

Average, 500 image pairs

Velocities and KE at $Y = 0$ (results from PDI drops)




Velocities and KE at $Y = 0$ (results from PDI drops)


Observations:

Lowest velocities occur along the centerline indicating the spray pattern resembles that of a hollow cone spray with recirculation.


Greatest velocities and turbulence are evident in the regions probed between injectors where the fuel spray from adjacent injectors mix.




$T_3 = 850^{\circ} \text{ F (728 K)}$
 $P_3 = 150 \text{ psia (1034 kPa)}$
 $\Phi = 0.45$



$T_3 = 850^{\circ} \text{ F (728 K)}$
 $P_3 = 200 \text{ psia (1379 kPa)}$
 $\Phi = 0.45$




$T_3 = 1030^{\circ} \text{ F (828 K)}$
 $P_3 = 150 \text{ psia (1034 kPa)}$
 $\Phi = 0.45$



50 m/s

$$KE = \frac{1}{2} (U_{RMS}^2 + V_{RMS}^2 + W_{RMS}^2)$$

Drop Size Differentiated Flows (Azimuthal Velocity)



Inlet Conditions:

$$T_3 = 1030^\circ F$$

$$\Delta P/P = 4\%$$

$$P_3 = 200 \text{ psia}$$

$$\Phi = 0.45$$

X = 3-mm from injector exit plane

Red = Small Droplets < 10 μm


Blue = Medium Droplets: > 10 μm , < 20 μm

Green = Large Droplets > 20 μm


Lowest velocities are noted at the center of the injector indicating the presence of a hollow cone spray. Only slight variations in azimuthal velocity between the three drop size ranges is evident in most locations.

Reference symbols:


$\rightarrow = 50 \text{ m/s}$



Comparing PDI and PIV, 9pt LDI



All nine injectors fueled vs center only (PIV)



$$P_3 = 150 \text{ psia}$$

$$T_3 = 650^\circ \text{ F}$$

9 fueled:

$$\phi_{inj} = \phi_{tot} = 0.45$$


19 lbm/hr/injector

Center fueled:

$$\phi_{inj} = 1.45$$

$$\phi_{tot} = 0.16$$

31 lbm/hr




Downstream
→

Alternate fuel testing in CE-5

The objectives of this experiment were to visually compare JP-8 flames with FT-2 (Sasol) flames for gross features. Specifically, we wanted to ascertain in a simple way visible luminosity, sooting, and primary flame length of the FT-2 compared to a standard JP grade fuel. We used video imaging and high-speed imaging to achieve these goals.


F-T fuel is from Sasol and produced from coal.



150 psia, Inlet Temperature 1030 F, 4% pressure drop, Fuel/Air Ratio=0.030

JP-8, 1030°F	JP-8, 850°F	JP-8, 650°F
50-50 blend, 1030°F	50-50 blend, 850°F	50-50 blend, 650°F
FT-2, 1030°F	FT-2, 850°F	FT-2, 650°F
Condition matrix used for alternative fuel flame imaging test.		

Alternate fuel test results, continued





Five successive frames at $T_3 = 850^\circ \text{ F}$ framed at 30kps that show flames burning JP-8 (top), the 50-50 blend (center) and FT-2. All images are unfiltered. The framing captures the flame from the center row of injectors and extends approximately 26-mm downstream. Flow passes from left to right.

Alternate fuel test results, continued



Average flame structure and luminous intensity obtained by averaging 1800 frames for the $T_3 = 1030^\circ F$ cases. The frame rate was 12 kps. Framing fully incorporates the center row, plus part of the top and bottom rows.

The axial span is approximately – 1.7-mm to 33-mm downstream from the injector exit. The frame height is approximately 39-mm.



Comparison showing average flame length and luminous intensity for $T_3 = 1030^\circ F$, for a 0.6-mm strip around the vertical center of the images shown at left.

Summary



- We use a variety of techniques to get information about the mixing and combustion environment for next-generation fuel-injector-mixer concepts
- Examples demonstrated some of the range and challenges for implementing optical tools in “realistic” combustor environments

Acknowledgment



- We thank the subsonic fixed wing project for sponsoring this work
- We also thank the CE-5 test crew

